

PRODUCT INSTALLATION SPECIFICATIONS:

Connection Type	Adhesive GripStrip
Free Floating Floor	Yes. DO NOT screw or nail moldings, transitions, cabinetry or vents through ANY allure flooring
Acclimation Period	48 hours minimum required in room prior to installation
Temperature Range	65°F to 85°F (18°C to 30°C) required in room of installation
During Acclimation & Install	After installation temps should stay between 55°F to 85°F (13°C to 30°C)
Interior Product Only	Yes. See limitations/exclusions below
Storage	Horizontally
Dye Lots	Yes. Install from a minimum of 3 to 4 different boxes and dye lots at one time. See page 3 of Owner's Manual for more information
Expansion Space	Yes. For room perimeters and fixed objects please leave 1/4" (6 mm) optimum space
Floor Flatness Tolerances	1/4" (6 mm) over 10' (3.05 m). Use floor leveler when exceeding tolerance
Hand Roller Required	Yes
75 lb min. Floor Roller	Yes
Moisture Reading Guidelines; OVER CONCRETE	Based on Tramex Concrete Moisture Encounter Plus Meter (scale 0% to 6%)
0% to 6%	Use a 6mil poly moisture barrier
Over 6%	DriCore recommended
Moisture Reading Guidelines; OVER WOOD	Never use 6 mil poly over wooden subfloors
Scale 0 to 13%	OK to install. Do not install above 13% moisture levels
Primer Over Wooden Subfloors	No
Basement Proofer over Concrete	No
Moisture Barrier (6 mil poly)	YES over concrete only.
Installs Over Radiant Flooring	Yes. Electric or hydronic approved — best practice recessed min 1/2" (12.7 mm) below finished floor. Do not turn thermostat above 85°F (30°C)
Suspended Wood Floors	Yes. 18" (45.72 cm) minimum well ventilated crawl space Use moisture barrier over ground/dirt Especially for mobile home installations
Foam/Cushioned Underlayment	No. Voids warranty if used in any application
Approved Subfloors - See Below	Must be smooth, solid, dry and no deflection
Wood	Yes. Solid, engineered, parquet (not over concrete)
Plywood	Yes. OSB & particleboard are approved for allure products only Luan is approved for all products
Vinyl	Yes, install over 1 layer of vinyl only. Linoleum, VCT, LVT, peel & stick
Concrete	Yes. Sealed, unsealed, poured in place gypsum On grade or below grade (see moisture guidelines)
Tile (Stone)	Yes. Ceramic, Terrazzo, stone tile (grout lines of less than 1/4" (6 mm) is optimum)
Dricore	Yes
Subfloors Not Approved	Carpet (any type), foam underlayment, cushioned back vinyl, rubber, cork, laminates, free-floating
Subfloor Approved Products	Basement Proofer - Custom Building Products RedGuard or TM Basement Proofer, Floor Leveler - Henry 554 & 555 Level Pro
Limitations/Exclusions	These types of installations will NOT be covered under warranty: All exterior installations & seasonal porches, boats/campers/RV's, sunrooms/solariums, non-temperature controlled rooms or homes
Steam Cleaner	DO NOT USE
Vertical Surfaces & Staircases	Not covered under warranty. Can be done using high quality construction adhesive. Product not intended for this usage
Limited Warranties	ALLURE TILE & PLANK limited 25-year residential ALLURE PLUS / CONTRACT limited lifetime residential / Limited 6-year light commercial ALLURE LARGE FORMAT 16X32 TILE limited lifetime residential / Limited 6-year light commercial